



PRODUCT PORTFOLIO

FLOOR COVERINGS 2024/25

creating better environments



FLOORING SYSTEMS

NUWAY
ENTRANCE
FLOORING

CORAL
ENTRANCE
FLOORING

MARMOLEUM
NATURAL
LINOLEUM

MARMOLEUM
MODULAR
NATURAL
LINOLEUM TILES

OFF THE
FLOOR
LINOLEUM

ALLURA
LUXURY
VINYL TILES

FAST FLOORING
ADHESIVE FREE
FLOORING

ETERNAL
GENERAL
PURPOSE
VINYL

SPHERA
HOMOGENEOUS
VINYL

STEP
SAFETY
VINYL

WETROOM
SOLUTIONS

ACOUSTIC
FLOORING
SOLUTIONS

ESD &
CLEANROOM
FLOORING

TESSERA
CARPET TILES

FLOTEX
FLOCKED
FLOORING

BESPOKE
& DESIGNER
COLLECTIONS

FURTHER
INFORMATION



grigio concrete
62523 | 50 x 50 cm
62513 | 100 x 100 cm



natural concrete
62522 | 50 x 50 cm
62512 | 100 x 100 cm



Brown RawTimber
60150FL5



grey autumn oak
60356 | 100 x 15 cm |  

		Allura 1.0	Allura 0.55
Total thickness	EN-ISO 24346	5mm	4mm
Wear layer thickness	EN-ISO 24340	1mm	0.55mm
Domestic use	EN-ISO 10874	Class 23	Class 23
Commercial use	EN-ISO 10874	Class 34	Class 33
Light industrial use	EN-ISO 10874	Class 42	Class 42
CE	EN 14041		
UK	BS EN 14041		
Reaction to fire	EN 13501-1	B _{fl} -s1, L, CS	B _{fl} -s1, L, CS
Thermal conductivity	EN 12524	0.25 W/mK	0.25 W/mK